

## Two burner Chinese range.

CC/02



Customized production only: both dimension and burners disposition are chosen by the client. Special stove for the oriental cooking with high performance burners: the vertical flame heats the pan uniformly, allowing a fast and complete cooking. Two burners can be chosen among: cast iron atmospheric burners with vertical flame (C KW 9,5 - T KW 14,0 - S KW 21,0) with gas safety valve taps, pilot flame and thermocouple. Pre-mixing radiant infra-red burner (B KW 23,0 110 Ac230V / 50Hz) with electronic flame control, adjustable flame 2 levels power KW 23,0 – KW 18,0. Removable burners to facilitate cleaning and maintenance. Structure in AISI 304 18/10 stainless steel AISI 304 18/10. Stainless steel cooking top thick 2,5 mm (reinforced): with runners equipped with cleaning system, that, in the wall stoves, is made by a front row of water sprays and by a drainage channel. Wall model. Removable drip-pans under the burners. Wok support rings (CERCHIO/CC) built in black enamelled cast iron. Round grids (GRIGLIA/CC) built in black enamel cast iron. AISI 304 18/10 stainless steel adjustable legs. CE/IMQ conformity certification.

TECHNICAL DATA	
Potenza forno a gas	11,3 kW
Width	1000 mm
Depth	700 mm
Height	850 mm
Volume	0,6 m3
Weight	107 Kg.
Gas Power	A scelta tra / Choosing between / On peut choisir entre / Es posible elegir entre / 9,5 - 14,0 - 21,0 - 23,0 kW kW
Burners	2
Burners Power	A scelta tra / Choosing between / On peut choisir entre / Es posible elegir entre / 9,5 - 14,0 - 21,0 kW (no price difference) - 23,0 kW (extra cost)
Diametro	Model "C", "T" 175 mm, model "S" 220 mm, model "B" 150 mm
Padelle raccogli gocce estraibili	Si
Piano liscio	Piano con canale posteriore con sistema di lavaggio del piano composto da canale con scarico e nr.1 fila di getti d'acqua
Colonnina	Colonnina con rubinetto acqua mm.500x700h con comando frontale

**FORHANDLER:**



**FastShop.dk**  
**35816700**

**S T O R K Ø K K E N U D S T Y R**