

Modular Cooking Range Line EV0700 4-Hot Plates Electric Boiling Top Range



ltem No.

To be installed on open base installations, bridging supports or cantilever systems. Four 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

ITEM #	Ľ
MODEL #	
NAME #	
SIS #	
AIA #	

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The four 2.6kW cast-iron plates are hermetically sealed to the one-piece top.
- The special design of the control knob system guarantees against water infiltration.
- IPX 4 water protection.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

APPROVAL:



Optional Accessories

optional Accessories	
 Junction sealing kit 	PNC 206086
• Support for bridge type installation, 800 mm	PNC 206137
• Support for bridge type installation, 1000 mm	PNC 206138
• Support for bridge type installation, 1200 mm	PNC 206139
• Support for bridge type installation, 1400 mm	PNC 206140
• Support for bridge type installation, 1600 mm	PNC 206141
• Frontal handrail 800 mm	PNC 206167
• Large handrail (portioning shelf) 800 mm	PNC 206186
Frontal handrail 1200 mm	PNC 206191
Frontal handrail 1600 mm	PNC 206192
Right and left side handrails	PNC 206240
 Water column with swivel arm (water column extension not included) 	PNC 206289
Water column extension	PNC 206291
Chimney upstand, 800 mm	PNC 206304
 2 side covering panels, height 250 mm, depth 700 mm 	PNC 206320
Chimney grid net, 400mm	PNC 206400





58 mm 2 1/4

9 7/8 ¹ 250 mm

0 15/16 " 24 mm

> EI EQ





_

			Front	Electric
	31 1/2 " 800 mm		_	Supply voltage: 372015 (Z7ECEH4R00) 372127 (Z7ECEH4R0N) Total Watts:
13 1/16 ⁻ 332 mm			EQ	Predisposed for:
_v	0		EI	372015 (Z7ECEH4R00)
		5/16 " D0 mm		Key Information
0 7/16 " 11 mm		2 1/16 " 52 mm	<u>) 7/16 "</u> 11 mm	Front Plates Power: Back Plates Power: Front Plates dimensions: Back Plates dimensions: Net weight: Shipping weight:
mm 58 mm 2 15/16 " 74 mm	27 21/10 22 27	9/16 " 700 mm	Side	372015 (Z7ECEH4R00) 372127 (Z7ECEH4R0N) Shipping height: 372015 (Z7ECEH4R00) 372127 (Z7ECEH4R00) Shipping width:
550 mm		(1 9	Shipping depth:
		mm		Shipping volume: 372015 (Z7ECEH4R00) 372127 (Z7ECEH4R0N) If appliance is set up or nex
EI	5 7/8 " 40 148 mm		→ 4 5/8 " 117 mm	If appliance is set up or nex furniture or similar, a safety maintained or some form o
	ical inlet (power) otential screw		Тор	
3 15/16 "		3 15/16 "		
				EV

380-400 V/3 ph/50/60 Hz 230 V/3 ph/50/60 Hz 10.4 kW

380-400V 3~ 50/60Hz

9-10,4kW

tion:

-	
Front Plates Power:	2.6 - 2.6 kW
Back Plates Power:	2.6 - 2.6 kW
Front Plates dimensions:	Ø 230 Ø 230
Back Plates dimensions:	Ø 230 Ø 230
Net weight:	40 kg
Shipping weight:	
372015 (Z7ECEH4R00)	39 kg
372127 (Z7ECEH4RON)	55 kg
Shipping height:	
372015 (Z7ECEH4R00)	530 mm
372127 (Z7ECEH4RON)	540 mm
Shipping width:	820 mm
Shipping depth:	860 mm
Shipping volume:	
372015 (Z7ECEH4R00)	0.37 m ³
372127 (Z7ECEH4RON)	0.38 m ³
17 H H H H	

or next to or against temperature sensitive a safety gap of approximately 150 mm should be form of heat insulation fitted.

Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.